

Winkeo-C

FIDO2 + QSCD

**Passwordless FIDO2 + PKI
USB-C token**



FIDO2 + QSCD products are compatible with the majority of deployed business applications.



Robust middleware

SafeSign Identity Client
(CSP/KSP/PKCS#11)



Integrated smart card (Mini SIM)

- Java Card™ JCOP4
- CC EAL6+
- DES/3DES, AES, ECC, RSA



Wide compatibility

- Strong authentication, directories, PKI, SSO, VPN, encryption, digital signature
- Windows 10/11 with Microsoft Entra ID, Google, GitHub... and identity federations such as Evidian, Ilex, Okta, Ping Identity...



Winkeo-C FIDO2 + QSCD is a USB-A token made in Europe. It integrates an eIDAS QSCD-certified PKI applet and a FIDO2 (CTAP 2.1) and FIDO U2F applet. Winkeo-C FIDO2 + QSCD thus allows users to benefit from high-quality logical security solutions as well as an extremely reliable qualified digital signature solution, while remaining easy to use.

- ✓ Meets European security requirements (eIDAS, QSCD, NIS, PSD2...)
- ✓ User presence by button
- ✓ Protection against phishing and preservation of the integrity of electronic documents
- ✓ No “key wrapping” / No shared key preinstalled

Interface(s)

- USB-C 2.0 PC/SC + HID

Smart card

- Micro SIM : ISO 7816 Java Card™ JCOP4 certified Criteria Common EAL6+

Supported Operating Systems

- Windows, Mac OS, Linux, Android, iOS

Browsers

- Edge, Firefox, Chrome, Safari

QSCD features

- Supported crypto-algorithms:
 - RSA 2K (bits)
 - RSA 3K (3072 bits)
 - RSA 4K (4096 bits)
 - ECC NIST P-256 / SECG secp256r1 (256 bits)
 - ECC NIST P-384 / SECG secp384r1 (384 bits)
 - ECC NIST P-521 / SECG secp521r1 (521 bits)
- Options:
 - PIN
 - PIN length between 5 and 15 bytes
 - PIN try limit set to 3
 - PUK
 - PUK length between 5 and 15 bytes
 - PUK try limit set to 3

FIDO2.0 / FIDO2.1 features

- Supported signature-algorithm:
 - ECC NIST P-256 / SECG secp256r1 (256 bits)
- Extensions:
 - credProtect
 - hmac-secret
 - credBlob (personalization option)
 - largeBlobKey (personalization option)
 - minPinLength (personalization option)
- Options :
 - rk (resident keys) - Discoverable credentials
 - Maximum number limited by available persistent memory (256 to 512 bytes per credential)
 - clientPIN, PIN protocol 1 and PIN protocol 2
 - PIN length between 4 and 63 bytes
 - PIN try limit set to 8. After 8 unsuccessful tries, the authenticator must be reset
 - No default value
 - ep - Enterprise Attestation (personalization option)
 - All options and extensions supported (pinUvAuthToken, authnrCfg, largeBlobs...)

Dimensions and weight

- Size: length 43.8 mm / width 18 mm / height 9.76 mm
- Weight: 5 g



About NEOWAVE and AET Europe

NEOWAVE and AET Europe solutions address the cybersecurity, digital trust and Identity Access Management markets. NEOWAVE is a French company, specializing in strong authentication and secure transactions. NEOWAVE products combine the high level of security provided by smart cards with the advantages of connectivity and storage technologies: USB, RFID / NFC and Bluetooth Low Energy (BLE).

AET Europe is a Dutch company, developing software solutions for user identification, authentication and digital signatures. AET Europe products are SafeSign IC, BlueX Certificate Management and ConsentID.